

Meet Bar

4K USB Camera with Soundbar

4K USB Video Camera with Soundbar to Make Life-like Conferencing

Meet Bar integrates a premium camera, microphone, and speakers into an All-in-One unit for a face-to-face video conferencing experience.

The camera's 120-degree wide-angle captures every participant in the conference room in high definition; The exclusive audio algorithm allows every word of the participant to be heard;

The flexible and easy installation simplifies conference room deployment, truly plug-and-play



Features & Benefits




See Everyone Clearly

- Adopts advanced image processing solution, 1/2.8" 8.42MP CMOS sensor, and high quality 12MP lens with 120-degree FOV, to provide sharp and crystal-clear image.
- Max resolution 2160p30 (MJPG/H.264/H.265).
- 4x electronic zoom adjustable.
- Auto-frame participants at meeting
- Type C USB port output high and low video resolution for different application scalable.



Hear Everyone Clearly

- Adopts beam forming microphone, and uses microphone array algorithms
- 360° Omni-directional and 5 meters voice pickup
- Full duplex communication
- 384ms acoustic echo cancellation and background noise suppression
- Auto-level loud and soft voices
- The peak-limiting algorithm eliminates even momentary speaker clipping to prevent distortion



Install and Operate Easily

- Comes with a mounting bracket, which can be placed above or below the monitor, or on the desktop of a conference room
- Audio and video integration, reduce wiring, simplify installation, USB plug and play, works with Windows, MAC OS, Android, Linux OS.
- Configured with remote control, users can set functions according to their preferences and needs
- Built-in standard UVC protocol, which can be used with any conference software you like

Product SPEC

Camera		Meet Bar
Part Number		TLC-800-U2-4K
Sensor		1/2.8-inch-high quality, 8.42-megapixel SONY CMOS sensor
Video Format	Type-C(USB2.0)	YUY2, NV12: 1280*720@15; 1024*576@20; 640*480@30;
		MJPG: 3840*2160@30; 2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30
		H.264, H.265: 3840*2160@20; 2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30
Digital Zoom		4X
Field of Viewing		120°
Minimum Lux.		0.7lux (50 IRE Max AGC, 1/30, F1.8)
Focal Length		f=2.20mm
Iris		F=2.2
Control Port		USB2.0(UVC/UAC)
Video Port		Type-C(USB2.0)
S/N Ratio		≥50dB
Image Parameters		
White Balance		Auto/Manual
Anti-Flicker		50HZ/60HZ/OFF
WDR		Supported
Edge Enhancement		Supported
Digital Noise Reduction		2D&3D
Image Flip		Supported
Electronic Pan/Tilt		Supported
Auto frame		Supported
Backlight Compensation		Supported
General		
Voice Pick Distance		3~5meters
USB Audio		Supported
Microphone		Omnidirectional microphone(100~16KHz)
Sensitivity		-26±2dB RL=2.2KΩ V5=2.0V
Input Voltage		DC+12V
Speaker		4Ω/8W 100-24KHz 2inch Anti-magnetic speaker
RJ45		POE(IEEE802.3af)
RJ45		POE(IEEE802.3af)
Color		Black/White
Dimension (L × W × H)		395mm×113mm×112mm
Net Weight		1kg(2.2LB)

Application



Board Room



Huddle Room



Small Room

Work With



Telcam Technology Co., Ltd

6 Floor, Building A, Shuanghuan Information Technology Industrial Park, No.8, Baoqing Rd, Longgang District, Shenzhen, 518116, China

Tel: +86-755-33275155

<http://www.telcam.com>