

Micro Converter SDI to HDMI 12G



The world's smallest 12G-SDI to HDMI broadcast quality converter! Blackmagic Micro Converter SDI to HDMI 12G is a miniaturized broadcast quality video converter that's been specifically designed for professional monitoring. It includes a 33 point 3D LUT for color calibrating any monitor, projector or television. Micro Converters feature full size HDMI and professional 12G-SDI connections for working with all NTSC, PAL, 720p, 1080p, 1080PsF, 1080i and 2160p rates, including 4K DCI at 24/47.95/48. You can power it over USB from a television or a mobile phone charger!

\$165

Connections

SDI Video Inputs

1

SDI Video Outputs

1 x loop out.

HDMI 2.0 Video Outputs

1 x type A.

SDI Rates


270Mb, 1.5G, 3G, 6G, 12G.

Multi Rate Support

Auto detection of SD, HD, 2K, Ultra HD and 4K.

Updates, Configurations and Power

USB Type-C.



Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p47.95,
1080p48, 1080p50, 1080p59.94,
1080p60
1080PsF25, 1080PsF29.97, 1080PsF30
1080i50, 1080i59.94, 1080i60

2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,
2Kp29.97 DCI, 2Kp30 DCI,
2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI,
2Kp59.94 DCI, 2Kp60 DCI
2KPsF25 DCI, 2KPsF29.97 DCI,
2KPsF30 DCI

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p47.95,
2160p48, 2160p50, 2160p59.94,
2160p60

4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,
4Kp29.97 DCI, 4Kp30 DCI,
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,
4Kp59.94 DCI and 4Kp60 DCI.

SDI Compliance

SMPTE 259M, SMPTE 292M,
SMPTE 296M, SMPTE 424M,
SMPTE 425M, SMPTE 2081-1,
SMPTE 2081-10, SMPTE 2082-1,
SMPTE 2082-10, SMPTE 2084
and SMPTE 2108-1

SDI Video Rates

SDI video connections are switchable
between standard definition, 720p,
1080i, 1080p, 2K DCI, Ultra HD and
4K DCI.

SDI Color Precision

4:2:2. A 33 point LUT can be loaded
via the software utility for calibrating
or improving monitor color.

SDI Color Space

YUV

SDI Auto Switching

Automatically detects SD, HD level A
or B for 3G-SDI, 2K DCI, Ultra HD and
4K DCI.

HDMI Video Standards

525i59.94 NTSC, 625i50 PAL
720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p47.95,
1080p48, 1080p50,
1080p59.94, 1080p60
1080i50, 1080i59.94, 1080i60
2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p47.95,
2160p48, 2160p50,
2160p59.94, 2160p60
4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,
4Kp29.97 DCI, 4Kp30 DCI,
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,
4Kp59.94 DCI and 4Kp60 DCI.

HDMI Color Precision

4:2:2. A 33 point LUT can be loaded
via the software utility for calibrating
or improving monitor color.

HDMI Color Space

YUV

Settings Control

Via MacOS™ and Windows™ software utility connected by USB.

Operating Systems



Mac 10.15 Catalina,
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

Software

Internal software upgrade via USB.

Power Requirements

Power Consumption
4W max.

Operational Voltage Range
4.4V to 5.25V DC


Environmental Specifications

Operating Temperature
0° to 40° C (32° to 104° F)

Storage Temperature
-20° to 60° C (-4° to 140° F)

Relative Humidity
0% to 90% non-condensing

Physical Specifications



What's Included

Micro Converter SDI to HDMI 12G

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2026, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller