

Air Fly for TriCaster

Built To Order

SKAARHOJ Air Fly - Live Switching Controller for TriCaster

The Air Fly for TriCaster offers an efficient and cost-effective control surface tailored for Vizrt TriCaster switchers. It boasts a user-friendly interface with fixed labels on keys for easy operation, six versatile four-way buttons with OLED displays for dynamic labeling or value display, a precise fader for seamless transition control, and additional user buttons for customized commands. Designed to enhance the workflow of video production with Vizrt TriCaster, the Air Fly brings reliability and efficiency to your production environment, ensuring smooth operations and professional results.



Benefits


- Optimized for Vizrt TriCaster, ensuring seamless integration and operation
- OLED displays on buttons for clear, customizable labels and values, enhancing user interaction
- Dedicated fader for smooth transition control, improving production quality
- User buttons offer customizable control, adapting to various production needs
- Cost-efficient solution for professional-grade video production, maximizing value

Features


- Dedicated for TriCaster
- Support for other devices
- Advanced ergonomics
- Versatile connectivity via IP
- Durable build quality
- 12 program and 12 preview buttons
- 12 menu selection buttons
- 6 programmable 4-way buttons with OLED screens
- Low profile durable transition fader
- Keyer section with all essentials
- Shift and user keys in large ME section
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested - adopted by professionals worldwide

Hardware Specifications	
Buttons	Elastomer Button (x53); Elastomer Four-Way Button (x2); Elastomer Four-Way Button w/Display (x6)
Analog Components	Slider 45mm (x1)
Programmable OLED Tiles	64x32 pixels (x6)
Other	LED-Bar, 3 steps (x6); LED (x1)
Connectivity	
Networking	1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
Power Supply	12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive PoE IEEE802.3af/t
Service Port	Micro USB for setting manual IP
Peripherals	USB-A 2.0 (500 mA) for Stream Deck, X-keys, additional networking adapters, frame grabbers etc.
Software	
Platform	Blue Pill (Reactor, Device Cores, skaarOS Linux)
Licenses	Full Reactor and Device Core licenses included
Physical and Shipping	
Product Weight	1376 g
Shipping Box Weight	2304 g
In The Box	(This Product) 12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive Getting Started Guide
Recommended Accessories (not included)	Ethernet Cable: Cat 6 S/FTP or better
Country of Origin	Denmark
EAN Code	5714074002819

Technical Drawings



310 mm
12.2"



178 mm
7"

72 mm
2,8"