

# Mini Fly

**Built To Order**

## SKAARHOJ Mini Fly – Universal Compact Switching Controller

The Mini Fly offers a super compact switching surface with 6 input buttons, a Cut/Auto button, a shift key, and a fader for transitions, embodying flexibility and efficiency. The top buttons feature OLED displays, showcasing the function or value of the key, while the Four-way buttons double as encoders for adjusting values. Designed with space-conscious applications and basic user needs in mind, especially where a transition fader is desired, the Mini Fly is an essential tool for enhancing control in a variety of production settings, from live events to studio work.



## Benefits

- Compact and efficient design for versatile use
- OLED displays on top buttons for clear function visibility
- Includes a fader for smooth transitions
- Four-way buttons double as encoders for precise adjustments
- Ideal for space-conscious applications and basic user needs

## Features

- Extensive list of supported devices
- Versatile connectivity via IP
- Durable build quality
- 6 program / preview buttons
- 6 button AUX/sends/macro/menu section
- Dedicated transition section with fader
- Multiple OLED displays for labels and feedback
- Universal control of multiple 3rd party devices
- User customization with Reactor Web UI
- 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)
- Designed and made in Denmark
- Time tested - adopted by professionals worldwide

| Hardware Specifications                |                                                                                                                                                                                                                                                                           |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Buttons                                | Elastomer Four-Way Button (x8); Elastomer Four-Way Button w/Display (x6)                                                                                                                                                                                                  |
| Analog Components                      | Slider 20mm (x1)                                                                                                                                                                                                                                                          |
| Programmable OLED Tiles                | 64x32 pixels (x6)                                                                                                                                                                                                                                                         |
| Other                                  | LED (x1); LED-Bar, 3 steps (x7); LED-Bar, 7 steps (x1)                                                                                                                                                                                                                    |
| Connectivity                           |                                                                                                                                                                                                                                                                           |
| Networking                             | 1G Ethernet w/Power over Ethernet (PoE IEEE802.3af/t)                                                                                                                                                                                                                     |
| Power Supply                           | 12V DC Jack 5.5mm x 2.1mm x 10mm Center Positive<br>PoE IEEE802.3af/t                                                                                                                                                                                                     |
| Service Port                           | Micro USB for setting manual IP                                                                                                                                                                                                                                           |
| Software                               |                                                                                                                                                                                                                                                                           |
| Platform                               | Blue Pill (Reactor, Device Cores, skaarOS Linux)                                                                                                                                                                                                                          |
| Licenses                               | Full Reactor and Device Core licenses included                                                                                                                                                                                                                            |
| Physical and Shipping                  |                                                                                                                                                                                                                                                                           |
| Product Weight                         | 288 g                                                                                                                                                                                                                                                                     |
| Shipping Box Weight                    | 780 g                                                                                                                                                                                                                                                                     |
| In The Box                             | (This Product)<br>12V Power Supply: Manufacturer: PHIHONG, Model Name: PSA15R-120P, Output: 12V/1.25A, Cable Length: 1.5m, Adapter type: EU, GB, US, AU depending on shipping country, DC Output Connector: 5.5mm x 2.1mm x 10mm Center Positive<br>Getting Started Guide |
| Recommended Accessories (not included) | Ethernet Cable: Cat 6 S/FTP or better                                                                                                                                                                                                                                     |
| Country of Origin                      | Denmark                                                                                                                                                                                                                                                                   |
| EAN Code                               | 5714074002956                                                                                                                                                                                                                                                             |

## Technical Drawings

